



# SPECIFICATIONS

## RESIDENTIAL SERIES M23



PRANA SERIA 160



PRANA SERIA 160 MINI



PRANA SERIA 210G



PRANA SERIA 210C

- The characteristics of equipment indicated in the documentation were obtained in laboratory conditions.
- Some of the content can be differ from device depending on model, region, software version and there is a possibility for changes without prior notice.
- For the required model searching, press the pointer next to the required model or scroll in the standard way.



PRANA SERIA 160 M23						
BALANCED VENTILATION	1/1 (NIGHT)	2/2	3/3	4/4 (REFERENCE FLOW)	5/5	BOOST
FLOW RATE M <sup>3</sup> /H	5/5	14/14	21/21	32/32	52/52	≤70
POWER INPUT (+\ -0,2W), W	3,2	4,3	5,2	7,3	16,4	26
SOUND PRESSURE LEVELS, INDOOR, 3M, LPA	8,2	18,5	23,7	32,5	44	-
SOUND PRESSURE LEVELS, OUTDOOR, 3M, LPA	<8	17,3	22,6	31,1	42,7	-
$\eta$ , +7°C	98,5	84,2	64,6	53,4	46,7	-
$\eta$ , -2°C	105,3	92	83,9*	65*	57,4*	-
$\eta$ , -15°C	99*	93*	87*	84*	76*	-
MINI-HEATING POWER INPUT (+\ -3W)	45					
DRAIN-HEATING POWER INPUT**	≥6					
*WINTER-MODE **OPTIONAL, MIN LENGTH						



PRANA SERIA 160 MINI M23						
BALANCED VENTILATION	1/1 (NIGHT)	2/2	3/3	4/4 (REFERENCE FLOW)	5/5	BOOST
FLOW RATE M <sup>3</sup> /H	5/5	14/14	21/21	32/32	52/52	≤70
POWER INPUT (+\ - 0,2W), W	3,2	4,3	5,2	7,3	16,4	26
SOUND PRESSURE LEVELS, INDOOR, 3M, LPA	8,2	18,5	23,7	32,5	44	-
SOUND PRESSURE LEVELS, OUTDOOR, 3M, LPA	<8	17,3	22,6	31,1	42,7	-
η, +7°C	79,4	69,9	52,6	43,1	37,2	-
η, -2°C	85,2	76,4*	58,6*	49,3*	42,4*	-
MINI-HEATING POWER INPUT (+\ -3W)	45					
DRAIN-HEATING POWER INPUT**	≥6					
*WINTER-MODE **OPTIONAL, MIN LENGTH						



PRANA SERIA 210G M23

BALANCED VENTILATION	1/1 (NIGHT)	2/2	3/3	4/4 (REFERENCE FLOW)	5/5	BOOST
FLOW RATE M <sup>3</sup> /H	5/5	20/20	28/28	38/38	65/65	≤85
POWER INPUT (+\ -0,2W), W	3,2	4	4,8	6,9	18,5	26
SOUND PRESSURE LEVELS, INDOOR, 3M, LPA	8	22,3	26,9	34,7	48,3	-
SOUND PRESSURE LEVELS, OUTDOOR, 3M, LPA	<8,5	20,2	24,8	33	45,5	-
$\eta$ , +7°C	95,1	86	70,7	55,9	51,6	-
$\eta$ , -2°C	115,8	92,9	81,2*	68,4*	60,4*	-
$\eta$ , -15°C	99*	90*	86*	83*	77*	-
MINI-HEATING POWER INPUT (+\ -3W)	45					
DRAIN-HEATING POWER INPUT**	≥6					
*WINTER-MODE **OPTIONAL, MIN LENGTH						



PRANA SERIA 210C M23						
BALANCED VENTILATION	1/1 (NIGHT)	2/2	3/3	4/4 (REFERENCE FLOW)	5/5	BOOST
FLOW RATE M <sup>3</sup> /H	7,5/7,5	25/25	35/35	48/48	90/90	≤140
POWER INPUT (+\ -0,2W), W	3,2	4,8	6,4	7,1	19,5	41,5
SOUND PRESSURE LEVELS, INDOOR, 3M, LPA	<9	23,4	29,4	34,1	48,6	-
SOUND PRESSURE LEVELS, OUTDOOR, 3M, LPA	<9	22,3	27,8	32	46	-
$\eta$ , +7°C	87,2	79,4	64,6	53,1	46,3	-
$\eta$ , -2°C	91,8	83,5*	72,9*	61,7*	53,4*	-
$\eta$ , -15°C	97*	92*	87*	86*	76*	-
MINI-HEATING POWER INPUT (+\ -3W)	45					
DRAIN-HEATING POWER INPUT**	≥6					
*WINTER-MODE **OPTIONAL, MIN LENGTH						





